



ALUMINUM BODY

MAXIMUM O.A.H. = 149.00" (12'-5.00")

MAXIMUM O.A.L. = 518.00" (43'-2.00")

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- VOGEL LUBE SYSTEM PUMP LOCATED IN COMPARTMENT P7 BEHIND ACCESS DOOR
- AIR INLET WITH DISCONNECT COUPLING LOCATED AT THE DRIVER SIDE STEP AREA
- 5/8" S/S SCUFFPLATE ON EACH CAB DOOR JAMB
- 5/8" S/S SCUFFPLATE ON REAR CAB CORNERS & FRONT CORNERS OF BODY
- FOUR 9" LED LIGHT STRIPS FOR SPEEDLAY LIGHTING
- AIR COMPRESSOR LOCATED BEHIND THE DRIVER'S SEAT
- BATTERY CHARGER LOCATED IN COMPARTMENT D4
- BATTERY CHARGE INDICATOR LOCATED ON D.S. SEAT RISER
- ONE 20V 120V DUPLEX RECEPTACLE LOCATED IN COMPARTMENT P5 AND ONE ON THE ENGINE TUNNEL
- ONE 12V L.E.D. LIGHT STRIP LOCATED ON EACH SIDE IN THE HOSEBED
- STAINLESS STEEL SCUFFPLATE AROUND HOSE CHUTE OPENINGS
- DRIP PAN GUARD FOR ROLL-UP DOOR IN COMPARTMENTS D1, D2, D3, P2, P3, P4, P5

- ELECTRIC DOOR LOCK ON COMPARTMENT P7 WITH KEY PAD IN COMPARTMENT P5
- PIERCE L.E.D. DUAL LIGHT STRIPS IN COMPARTMENT D1, D2, D3, D4, D6, P1, P2, P3, P4, P5, P7
- 9" PIERCE L.E.D. LIGHT STRIP IN COMPARTMENT D5, P6
- RACK FOR CYLINDER STORAGE IN COMPARTMENT P2
- PAINTED SHELF TRACKS LOCATED IN COMPARTMENT D1, D2, D3, D4, P1, P2, P3, P4, P5, P7
- ONE ADJUSTABLE SHELF (FULL DEPTH/FULL WIDTH) IN COMPARTMENT D2, D4, P1, P2, P3 & TWO IN P5, P7
- ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT D1, D3
- ONE ADJUSTABLE VERTICAL PARTITION IN COMPARTMENT D1
- RACK FOR AIR BAGS PLUS NYLON STRAP FOR ADDITIONAL BAGS IN COMPARTMENT D1
- SWING-OUT TOOL BOARD WITH PEGBOARD PATTERN IN COMPARTMENT P4
- 12V 300 WATT ELECTRIC HEATER IN COMPARTMENT P7
- CIRCUIT BREAKER PANEL IN COMPARTMENT D4

- GENERATOR METER PANEL LOCATED ON THE PUMP PANEL
- STABILIZER COMPARTMENTS MODIFIED FOR 18" GROUND PENETRATION
- STABILIZERS MODIFIED FOR 18" GROUND PENETRATION
- AERIAL PEDESTAL RAISED 8.50"
- SLIDE-ON STABILIZER PADS
- TRIDENT FOLDING STEPS MOUNTED ON AERIAL DEVICE PER SHOP ORDER
- TECNIQ L.E.D. RING STYLE LIGHTING ON AERIAL LADDER SECTIONS
- L.E.D. LIGHTING ON AERIAL AT EGRESS
- 120V POWER TO AERIAL TIP
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNTABLE
- LIFTING EYE RESCUE ATTACHMENT AT AERIAL TIP

REV	DATE	BY	CH	QUANTUM
110EC15	RPA	JBO	MAKE	
06NOV15	RPA	JBO	PIERCE	
22JUN15	TKA	GRM	MODEL	

		JOB NO.	29065
		SCALE	DATE
CHASSIS DATA TITLE 105 AERIAL LADDER & BODY ASSEMBLY (105 HSL) 525 GALLON TANK, 500 GAL. WATER, 25 GAL. FOAM FOR CITY OF WAUKESHA FIRE DEPARTMENT WAUKESHA, WI DWG NO. 29065AD	DATE	09JUN15	
	CHECKED BY	GRM	
	SHEET SIZE	D	
	SHEET NO.	1 OF 1	