

PUMPER
BODY

Long Aluminum 2nd Gen Pumper

CHASSIS
Enforcer Chassis

CHASSIS
AXLE, FRONT, CUSTOM

20,000 Lb Dana Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

19" Extended Painted Steel

CAB

7010 Enforcer Cab

BODY
WATER TANK

1000 Gallon Poly Water Tank

COMPT, PUMPER, REAR

44.50" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

171" RollUp Full Height Front & Rear FDLR

COMPT, PUMPER PASS. SIDE

171" RollUp Full Height Front & Rear FDLR

FIRE SUPPRESSION
PUMPHOUSE

45" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

SpeedLays Not Required

GENERATOR

Generator Not Required

Foam System

Husky 3 Single Agent Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water

Side Roll and Frontal Impact Protection

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

- ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED IN COMPARTMENT D3
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER
- NINE ADJUSTABLE SHELVES LOCATED PER SHOP ORDER
- TWO FLOOR MOUNTED SLIDE-OUT TRAYS LOCATED PER SHOP ORDER
- ONE SWING-OUT TOOLBOARD LOCATED PER SHOP ORDER
- ONSPOT AUTOMATIC TIRE CHAINS
- TWO VERTICAL PARTITIONS LOCATED PER SHOP ORDER

Side View Dimensions:
Overall Length: 94.50' (Cab to Rear of Body) + 40.50' (Cab to Front of Body)
Overall Width: 125.00' (10'-5") APPROX O.A.H.
Wheelbase: 139.50'
Body Length: 155.50'
Rear Overlap: 6.00'

Front View Dimensions:
Overall Width: 125.00' (10'-5") APPROX O.A.H.
Wheelbase: 139.50'
Body Length: 155.50'

Rear View Dimensions:
Overall Width: 88.00'
Overall Length: 70.00'
Wheelbase: 205.00' WB
Overall Length (Approx): 391.00' (32'-7.00") APPROX OAL

Labels and Components:
(1) WHELEN PSTANK L.E.D. WATER LEVEL INDICATOR EACH SIDE
PIERCE SIDE VIEW CAMERA
WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
(1) WHELEN PIONEER L.E.D. VISOR LIGHT
(1) WHELEN M6 L.E.D. WARNING LIGHT
(1) WHELEN M6 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
(1) FEDERAL Q2B SIREN
(2) GROVER AIR HORNS
(1) WHELEN SA31SP SPEAKER WITH 5/STL GRILLE
CENTER HOSE TRAY FOR 125" OF 1.75" HOSE
(3) WHELEN M6V2 L.E.D. WARNING LIGHTS EACH SIDE
(2) WHELEN PFBP12C L.E.D. DECK LIGHTS
(2) WHELEN L31HRN L.E.D. WARNING LIGHTS
(2) HOSE BED DIVIDERS
(1) WHELEN TANF65 L.E.D. TRAFFIC DIRECTING LIGHT RECESSED W/ 5/STL TRIM
(1) CUP SWITCH FOR REAR WORK LIGHTS
(2) WHELEN M6 L.E.D. STOP/TAI LIGHTS
DIRECTIONAL LIGHTS BACK-UP LIGHTS WARNING LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS
HYDRAULIC LADDER RACK FOR CTF DUO-SAFETY LADDERS:
(1) 28" 2 SECTION 1200A
(1) 14" ROOF 775A
(1) 10" FOLDING 585A
(2) PIKE POLE TUBES
(2) CTF 6.00" X 10" H.S.H.
PIERCE REAR VIEW CAMERA (RECESSED)
(1) 2.50" OUTLET
5'-7" HUMAN FIGURE FOR SCALE

 MANUFACTURING INC.		JOB NO.	31398 01-02
		SCALE	DATE
		DRAWN BY	21MAR17
		COL	
		CHECKED BY	24MAR17
		SHE	
		SHEET SIZE	SHEET NO.
		D	1 OF 1

		CHASSIS DATA		TITLE	Pierce Pumper Approval Drawing
		MAKE		FOR	-
		PIERCE			
		MODEL		DWG NO.	31398AD
		ENFORCER			

View File Created 25-JUL-2017 14:01:48