

PUMPER
BODY

Long Aluminum 2nd Gen Pumper

CHASSIS
Enforcer Chassis

CHASSIS
AXLE, FRONT, CUSTOM

18,000 Lb Meritor Axle

AXLE, REAR

24,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

22" Extended Steel Painted, Underslung

CAB

6010 Enforcer Cab

BODY
WATER TANK

750 Gallon Poly Water Tank

COMPT, PUMPER, REAR

44.50" FF RollUp Rear Compt, Flush Rear, 25.88" Deep

COMPT, PUMPER, DRIVER SIDE

161" RollUp Full Height & Depth Front & Rear

COMPT, PUMPER PASS. SIDE

161" RollUp Full Height & Depth Front & Rear

FIRE SUPPRESSION
PUMPHOUSE

56" Control Zone Side Mount

PUMP

2000 GPM Hale QMAX

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Foam System Not Required

Foam Cell

Foam Cell Not Required

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON D.S. CAB CORNER

3. AIR INLET WITH DISCONNECT COUPLING IN DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED BEHIND DRIVERS SEAT

5. BATTERY CHARGE INDICATOR LOCATED ON D.S. CAB CORNER

6. THREE FLOOR MOUNTED SLIDE-OUT TRAYS LOCATED PER SHOP ORDER

7. HANNAY BOOSTER REEL MODEL: SBEP24-28-23 WITH CAPACITY FOR 200' OF 1.00" BOOSTER HOSE LOCATED IN CARGO AREA ABOVE PUMP

8. NINE ADJUSTABLE SHELVES LOCATED PER SHOP ORDER

9. LITTLE GIANT LADDER MODEL 13 LOCATED ON FLOOR IN COMPARTMENT D1

10. PAC TRAC LOCATED PER SHOP ORDER

11. PARTITION BETWEEN COMPARTMENTS D1/R1 AND P1/R1

12. ONE TILTING/SLIDE-OUT TRAY LOCATED PER SHOP ORDER

13. ONE HORIZONTAL PARTITION LOCATED PER SHOP ORDER

14. RETENTION NETTING LOCATED PER SHOP ORDER

Side View Dimensions:
Overall Length: 393.50 (32'-9.50") APPROX OAL
Overall Width: 86.00
Wheelbase: 195.00 WB
Front Overlap: 57.62 FC
Rear Overlap: 28.00
Ground Clearance: 8.00" NFPA MIN.
Cab Length: 91.00
Engine Compartment Length: 60.00
Pump Compartment Length: 75.50
Storage Compartment Length: 41.00
Water Tank Length: 139.50
Water Tank Width: 70.00
Water Tank Depth: 25.88
Water Tank Volume: 750 Gallon Poly Water Tank
Water Tank Material: 44.50" FF RollUp Rear Compt, Flush Rear, 25.88" Deep

Front View Dimensions:
Overall Width: 86.00
Overall Height: 118.00 (9'-10") APPROX O.A.H.
Water Level Indicator Light: (1) FRC MAXVISION L.E.D. WATER LEVEL INDICATOR LIGHT EACH SIDE
Wheeler Pioneer L.E.D. Scene Lights: (2) WHELEN PIONEER L.E.D. SCENE LIGHTS EACH SIDE
Wheeler Freedom IV 72" L.E.D. Lightbar: (1) WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
Retrac Heated/Remote Control Mirrors with Convex Section: RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
Wheeler MG L.E.D. Warning Lights: (2) WHELEN MG L.E.D. WARNING LIGHTS EACH SIDE
Wheeler MG L.E.D. Directional Light in a Common Bezel Each Side: (1) WHELEN MG L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
Federal Q2B Siren: (1) FEDERAL Q2B SIREN
Wheeler SA31SP Speakers with 5/STL Grilles: (2) WHELEN SA31SP SPEAKERS WITH 5/STL GRILLES
Bumper Crosslay for 150' of 1.75" Hose: (1) BUMPER CROSSLAY FOR 150' OF 1.75" HOSE
Grove Air Horns: (2) GROVER AIR HORNS

Top View Dimensions:
Overall Length: 393.50 (32'-9.50") APPROX OAL
Overall Width: 86.00
Water Tank Length: 139.50
Water Tank Width: 70.00
Water Tank Depth: 25.88
Water Tank Volume: 750 Gallon Poly Water Tank
Water Tank Material: 44.50" FF RollUp Rear Compt, Flush Rear, 25.88" Deep

Equipment Labels:
(1) WHELEN PELCC L.E.D. SCENE LIGHT EACH SIDE
(3) FRP L.E.D. LIGHTS FOR DESIGNATED WALKING AREA
(2) WHELEN MG L.E.D. WARNING LIGHTS EACH SIDE
(2) WHELEN MG L.E.D. WARNING LIGHTS
(1) CUP SWITCH FOR REAR WORK LIGHTS
(2) WHELEN MG L.E.D. STOP/TAI LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN MG PIERCE BEZELS
(1) CUP SWITCH FOR REAR WORK LIGHTS
(1) 24" DUO-SAFETY 2-SECTION 900A
(1) 14" DUO-SAFETY ROOF 775-DR
(1) 10" DUO-SAFETY FOLDING 595A
(1) BACKBOARD (2" X 16" X 72")
(2) PIKE POLE TUBES
(1) WHELEN TAL6S L.E.D. TRAFFIC DIRECTING LIGHT RECESSED W/ 5/STL TRIM
(2) WHELEN PELCC L.E.D. WORK AREA LIGHTS
(4) HOSE BED DIVIDERS
(2) 2.50" OUTLETS
(1) WHELEN TAL6S L.E.D. TRAFFIC DIRECTING LIGHT RECESSED W/ 5/STL TRIM
(2) WHELEN PELCC L.E.D. WORK AREA LIGHTS

Hosebed Capacity:
BED 1
400' OF 2.50" D.J. POLY HOSE
BED 2
1000' OF 5.00" D.J. POLY HOSE
BED 3
200' OF 2.50" D.J. POLY HOSE
BED 4
200' OF 2.50" D.J. POLY HOSE WITH 200' OF 1.75" D.J. POLY HOSE ABOVE

 MANUFACTURING INC.		JOB NO.	31839
		SCALE	1:24
		DATE	
		DRAWN BY	COL
		CHECKED BY	KB0
		SHEET SIZE	D
		SHEET NO.	1 OF 1

Pierce Pumper Approval Drawing		TITLE	Pierce Pumper Approval Drawing
Conway Fire Department		FOR	Conway Fire Department
DWG NO.		31839AD	

View File Created 06-NOV-2017 11:23:53