

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb TAK-4 Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

22" Extended Painted Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

1000 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

Tool Compartment

COMPT, PUMPER, DRIVER SIDE

152" Lap Full Height Front & Rear FOLER

COMPT, PUMPER PASS. SIDE

152" Lap Low FOLER

FIRE SUPPRESSION

PUMPHOUSE

45" Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity, Single Stock

CROSSLAYS, 2.50"

2.50" Crosslay Not Required

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Foam System Not Required

Foam Cell

Foam Cell Not Required

Side Roll and Frontal Impact Protection

Side elevation drawing of the Pumper Body. Key dimensions include a height of 30.75 and 29.00 for the rear section, and a width of 64.00 and 88.00 for the main body. A label indicates '(1) 6.00" X 10" HARD SUCTION HOSE THROUGH EACH SIDE'.

Top-down view of the Pumper Body. Key dimensions include a width of 40.00, 66.50, and 34.50, and a length of 152.00. A label indicates '(1) 6.00" X 10" HARD SUCTION HOSE THROUGH EACH SIDE'.

Front elevation drawing of the Pumper Body. Key dimensions include a height of 119.00 (9'-11") APPROX O.A.H., a width of 91.00, and a length of 184.50 WB and 373.50 (31'-1.50") APPROX OAL. A label indicates '(1) 6.00" X 10" HARD SUCTION HOSE THROUGH EACH SIDE'.

Front view of the Pumper Cab. Key dimensions include a height of 21.50" L.E.D. LIGHTBARS, a width of 21.50" L.E.D. LIGHTBARS, and a length of 21.50" L.E.D. LIGHTBARS. A label indicates '(1) 6.00" X 10" HARD SUCTION HOSE THROUGH EACH SIDE'.

HOSEBED CAPACITY	
BED 1	500' OF 3.00" D.J. POLY HOSE
BED 2	400' OF 5.00" D.J. POLY HOSE
BED 3	600' OF 5.00" D.J. POLY HOSE
BED 4	500' OF 3.00" D.J. POLY HOSE

Rear view of the Pumper Body. Key dimensions include a height of 72.00, a width of 14.00, 68.00, and 14.00, and a length of 96.00. A label indicates '(1) 6.00" X 10" HARD SUCTION HOSE THROUGH EACH SIDE'.

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB					
2. AIR INLET WITH DISCONNECT COUPLING IN DRIVER SIDE PUMP PANEL					
3. BATTERY CHARGER LOCATED BEHIND DRIVERS SEAT					
4. BATTERY CHARGE INDICATOR DISPLAYED THRU DRIVER SIDE CAB WINDOW					
5. TWO ADJUSTABLE SHELVES LOCATED PER SHOP ORDER					

 MANUFACTURING INC.		JOB NO.	33082
SCALE		1:24	DATE
DRAWN BY		COL	090CT18
FOR		KBO	090CT18
SHEET SIZE		D	SHEET NO. 1 OF 1

TITLE	Pierce Pumper Approval Drawing
FOR	GFEC Field Stock Unit
DWG NO.	33082AD

CHASSIS DATA	MAKE	PIERCE
MODEL	ENFORCER	

REV	DATE	BY	CH
03DEC18	COL	KBO	
31OCT18	COL	KBO	

View File Created 19-DEC-2018 12:02:57