



HOSEBED CAPACITIES

- ① 600' OF 2.50" D.J. POLY HOSE
- ② 300' OF 1.75" D.J. POLY HOSE
- ③ 1000' OF 4.00" D.J. POLY HOSE
- ④ 600' OF 2.50" D.J. POLY HOSE

ALUMINUM BODY

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. AIR INLET WITH DISCONNECT COUPLING LOCATED IN FORWARD IN THE DS STEP WELL
- 2. BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
- 3. BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER
- 4. DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- 5. ALL FOLDING STEPS TO BE TRIDENT WITH INTEGRATED L.E.D. LIGHT UNLESS SPECIFIED
- 6. ONE HANNAY ELECTRIC REWIND CORD REEL WITH 200' OF 10/3 MODEL 1618-17-18 LOCATED ABOVE RS3 COMPARTMENT

REV	DATE	BY	CH	ENFORCER
▽	27APR21	JRC	CSH	CHASSIS DATA
▽	25MAR21	JRC	CSH	MAKE
▽	11FEB21	KLE	EGO	PIERCE
▽	05JAN21	KLE	EGO	MODEL

		JOB NO.	35788
		SCALE	1:24
TITLE 1250-D-500G WATERTANK, 163" FHFD HDRP BODY LADDER RACK THRU BODY, (2) XLAYS, GENERATOR	FOR	CITY OF DANVILLE DANVILLE, VIRGINIA	DATE
	DWG NO.	35788AD-SH1	
	CHECKED BY	EGO	18DEC20
	SHEET SIZE	D	SHEET NO. 1 OF 2