

Pumper, PUC

BODY

Pumper, PUC, Aluminum

CHASSIS

Enforcer Chassis, PUC

CHASSIS

AXLE, FRONT, CUSTOM

22,800 Lb TAK-4 Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

500 HP Cummins X12 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

22" Extended Painted Steel

CAB

7010 Enforcer Cab, PUC

BODY

WATER TANK

1000 Gallon Poly Water Tank

COMPT, PUMPER, REAR

33.50" FF RollUp Rear Compt w/Tailboard, PUC

COMPT, PUMPER, LEFT SIDE

214" RollUp Full Height & Depth Front & Rear, PUC

COMPT, PUMPER, RIGHT SIDE

214" RollUp Full Height & Depth Front & Rear, PUC

FIRE SUPPRESSION

PUMPHOUSE

Control Zone, PUC

PUMP

1500 GPM Pierce PUC

CROSSLAYS, 1.50"

(2) 1.50", Poly Trays, 200'

CROSSLAYS, 2.50"

(1) 2.50", Poly Tray, 200'

GENERATOR

Generator Not Required

Foam System

Husky 3 Single Agent Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water, PUC

Side Roll and Frontal Impact Protection

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CREW CAB

3. AIR INLET WITH KUSSMAUL AIR EJECT LOCATED ON DRIVER SIDE OF THE CREW CAB RECESSED

4. BATTERY CHARGER LOCATED IN CAB PER SHOP ORDER

5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER

6. EIGHT ADJUSTABLE SHELVES LOCATED PER SHOP ORDER

7. FIVE FLOOR MOUNTED SLIDE-OUT TRAY LOCATED PER SHOP ORDER

8. TWO TILT/SLIDE-OUT TRAYS LOCATED IN COMPARTMENT PER SHOP ORDER

9. ONE SLIDE-OUT TOOLBOARD LOCATED PER SHOP ORDER

10. ONE VERTICAL PARTITION LOCATED IN COMPARTMENT PER SHOP ORDER

11. ONE 120V 6-PLACE RECEPTACLE STRIP LOCATED PER SHOP ORDER

12. FOUR 120V 4-PLACE RECEPTACLES LOCATED PER SHOP ORDER

13. AIR OUTLET WITH SHUT-OFF VALVE LOCATED DRIVER SIDE STEP WELL

14. ONE PEGBOARD ON BACK WALL IN COMPARTMENT PER SHOP ORDER

Side View Dimensions:
Overall Length: 407.50 (33'-11.50") APPROX OAL
Wheelbase: 213.50 WB
Front Overlap: 33.00
Rear Overlap: 33.00
Total Width: 99.00
Height: 125.00 (10'-5") APPROX O.A.H.

Top View Dimensions:
Overall Length: 175.50
Overall Width: 96.00
Wheelbase: 156.50
Front Overlap: 19.00
Rear Overlap: 75.00
Height: 21.00

Rear View Dimensions:
Overall Width: 98.00
Height: 70.00
Wheelbase: 42.00
Front Overlap: 28.00
Rear Overlap: 28.00

Equipment Callouts:
(1) CSS SIDE VIEW CAMERA (RECESSED)
(1) PIERCE SIDE VIEW CAMERA
(1) WHELEN PIONEER L.E.D. VISOR LIGHT
(1) WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
(1) WHELEN M6 L.E.D. WARNING LIGHT
(1) WHELEN CBT L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
(1) FEDERAL Q2B SIREN
(2) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE
(1) WHELEN SA31SP SPEAKER WITH 5/5TL GRILLE
UNDERSLUNG BUMPER TRAY FOR 100' OF 1.75" HOSE WITH ALUMINUM TREADPLATE COVER
(2) HOSE BED DIVIDERS
COMPARTMENT FOR: (1) 10" PIKE POLE W/D-HANDLE, (1) 6" PIKE POLE W/D-HANDLE, (1) TROUGH FOR 10" PIKE POLE
(2) WHELEN M6 L.E.D. WARNING LIGHTS
(1) 2.50" OUTLET
(2) WHELEN M9 L.E.D. SCENE LIGHTS
PIERCE REAR VIEW CAMERA (RECESSED)
STOP TAIL-BACK-UP & DIRECTIONAL L.E.D. LIGHTS IN A COMMON BEZEL
MARKER LIGHT WITH RUBBER ARM EACH SIDE
(2) WHELEN M6 L.E.D. WARNING LIGHTS
(1) CUP SWITCH FOR REAR SCENE LIGHTS
(1) CUP SWITCH FOR HOSE BED LIGHTS
LADDER STORAGE FOR DUO-SAFETY LADDERS: (1) 24" 2 SECTION 900A, (1) 14" ROOF 775A
COMPARTMENT FOR: (1) 10" FOLDING LADDER, (1) HARD SUCTION HOSE, (1) HARD SUCTION HOSE TROUGH

		JOB NO.	36080
MANUFACTURING INC.		SCALE	1:24
		DATE	
TITLE		DRAWN BY	MMF
Pierce PUC Pumper Approval Drawing		CHECKED BY	COL
FOR		SHEET NO.	1 OF 1
Huntington Fire Department		SHEET SIZE	D
DWG NO.			

CHASSIS DATA	MAKE	PIERCE	MODEL	ENFORCER
12MAR21	MMF	ZWE	17FEB21	MMF
17FEB21	MMF	GKH	11FEB21	MMF
11FEB21	MMF	DT5		
REV	DATE	BY	CH	

36080AD

View File Created 15-MAR-2021 08:06:20