

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

19,500 Lb TAK-4 Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

22" Extended Painted Steel

CAB

7000 Enforcer Cab

BODY

WATER TANK

1000 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

28.75" FF RollUp Rear Compt

COMPT, PUMPER, LEFT SIDE

152" Lap Full Height Front & Rear FDLER

COMPT, PUMPER, RIGHT SIDE

152" Lap Low FDLER

FIRE SUPPRESSION

PUMPHOUSE

45" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity Mercedes Hose

CROSSLAYS, 2.50"

2.50" Crosslay Not Required

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Foam System Not Required

Foam Cell

Foam Cell Not Required

Side Roll and Frontal Protection

Technical drawing of a fire truck showing side, front, and top views with dimensions and callouts for various components like lights, mirrors, and hoses.

Side View Callouts:

- (1) HIWIZ FT-B-72 L.E.D. VISOR LIGHT
- WHELEN FREEDOM IV 21.5" L.E.D. LIGHTBAR EACH SIDE
- (1) HIWIZ FT-B-72 L.E.D. VISOR LIGHT
- WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN M6 L.E.D. WARNING LIGHT
- (1) WHELEN M6 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (1) FEDERAL ES100C SPEAKER WITH STAINLESS STEEL ESFMT-EF GRILL
- (1) WHELEN M6 L.E.D. WARNING LIGHT EACH SIDE (RECESSED)
- (2) GROVER AIR HORNS
- LEFT HOSE TRAY FOR 140" OF 1.75" HOSE
- (1) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE
- FREE FLOATING RUNNING BOARD HOSE TRAY FOR 25" OF 5.00" HOSE
- (2) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE

Front View Callouts:

- (1) HIWIZ FT-B-72 L.E.D. VISOR LIGHT
- WHELEN FREEDOM IV 21.5" L.E.D. LIGHTBAR EACH SIDE
- (1) HIWIZ FT-B-72 L.E.D. VISOR LIGHT
- WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN M6 L.E.D. WARNING LIGHT
- (1) WHELEN M6 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (1) FEDERAL ES100C SPEAKER WITH STAINLESS STEEL ESFMT-EF GRILL
- (1) WHELEN M6 L.E.D. WARNING LIGHT EACH SIDE (RECESSED)
- (2) GROVER AIR HORNS
- LEFT HOSE TRAY FOR 140" OF 1.75" HOSE

Top View Callouts:

- (1) HIWIZ FT-MB-24-TRGWA L.E.D. SCENE LIGHT EACH SIDE
- (2) WHELEN M6 L.E.D. WARNING LIGHTS
- (2) WHELEN MICRO PIONEER MP** L.E.D. SCENE LIGHTS
- (4) 0.25" HOSE BED DIVIDERS
- (3) 2.50" OUTLETS
- (1) CUP SWITCH FOR REAR SCENE LIGHTS
- (1) CUP SWITCH FOR HOSEBED LIGHTS
- (2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS
- DUO-SAFETY LADDERS: (1) 24" 2-SECTION 900A (1) 14" ROOF 775A (1) 10" FOLDING 585A (2) ALUMINUM NY PIKE POLE TUBES
- (1) BRITAX MODEL 428 L.E.D. MARKER LIGHT EACH SIDE
- PIERCE REAR VIEW CAMERA RECESSED

HOSEBED CAPACITY

BED	Capacity
BED 1	200' OF 1.75" D.J. POLY HOSE
BED 2	400' OF 1.75" D.J. POLY HOSE
BED 3	1200' OF 5.00" Mercedes Mega Flow HOSE
BED 4	400' OF 3.00" D.J. POLY HOSE
BED 5	400' OF 2.50" D.J. POLY HOSE

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

- ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED ON TOP OF BUMPER LEFT SIDE
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED IN COMPARTMENT PER SHOP ORDER
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER

CUSTOMER APPROVAL				Pierce MANUFACTURING INC.		JOB NO.	37196
APPROVED BY: _____						SCALE	DATE
DATE: _____						1:24	
				TITLE	Pierce Pumper Approval Drawing	DRAWN BY	28FEB22
				MAKE	-	MMF	
				FOR	Glick Fire equipment Co Inc	CHECKED BY	28FEB22
				MODEL	-	COL	
				DWG NO.	37196AD	SHEET SIZE	SHEET NO.
REV				DATE		D	1 OF 1
				BY			
				CH			
				ENFORCER			

View File Created 01-MAR-2022 07:42:37