

PUMPER
BODY

Long Aluminum 2nd Gen Pumper

CHASSIS
Enforcer Chassis

CHASSIS
AXLE, FRONT, CUSTOM

20,000 Lb Dana Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

500 HP Cummins X12 Engine

TRANSMISSION

Allison 5th Gen, 4000 EVS P

BUMPER

19" Extended Stainless Steel

CAB

7010 Enforcer Cab

BODY
WATER TANK

1000 Gallon Poly Water Tank

COMPT, PUMPER, REAR

37.75" FF RollUp Rear Compt

COMPT, PUMPER, LEFT SIDE

171" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER, RIGHT SIDE

171" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION
PUMPHOUSE

48" Control Zone Side Mount

PUMP

1500 GPM Hale QMAX

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

SpeedLays Not Required

GENERATOR

Generator Not Required

Foam System

Husky 3 Single Agent Foam System

Foam Cell

20 Gallon Foam Cell, Reduced Water

Side Roll and Frontal Impact Protection

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED IN COMPARTMENT PER SHOP ORDER

5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER

6. FIVE ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER

7. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT PER SHOP ORDER

8. ONE CTECH FOUR DRAWER ASSEMBLY LOCATED PER SHOP ORDER

PIERCE SIDE VIEW CAMERA

EQUIPMENT RACK-SWITCH PANEL

HYDRAULIC LADDER RACK-CYLINDER PUMP ACCESS

FREE FLOATING RUNNING BOARD HOSE TRAY FOR 25' OF 5.00" HOSE

WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR

RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION

(1) WHELEN M6 L.E.D. WARNING LIGHT
(1) WHELEN C6T L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE

(3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE

(1) WHELEN PIONEER L.E.D. VISOR LIGHT

(2) AIR HORNS

(1) WHELEN SA315P SPEAKER WITH 5/STL GRILLE

CENTER HOSE TRAY FOR 125' OF 1.75" HOSE

HOSEBED CAPACITY
BED 1
1000' OF 5.00" D.J. POLY HOSE
BED 2
600' OF 2.50" D.J. POLY HOSE
BED 3
600' OF 2.50" D.J. POLY HOSE

(2) WHELEN PIONEER L.E.D. SCENE LIGHTS EACH SIDE

(2) WHELEN L31HRN L.E.D. WARNING LIGHTS

(1) WHELEN TAL65 L.E.D. TRAFFIC DIRECTING LIGHT

(2) WHELEN M6 L.E.D. SCENE LIGHTS RECESSED

(1) 2.50" OUTLET

(1) 2.50" TANK FILL 21.75 TYP

(1) CUP SWITCH FOR REAR SCENE LIGHTS

(1) CUP SWITCH FOR HOSEBED LIGHTS

(2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS

(2) WHELEN 700 L.E.D. SCENE LIGHTS

DUO-SAFETY LADDERS:
(1) 24" 2 SECTION 900A
(1) 14" ROOF 775A
(1) 10" FOLDING 585A
(2) ALUMINUM PIKE POLE TUBES

(2) WHELEN M6 L.E.D. WARNING LIGHTS RECESSED

PIERCE REAR VIEW CAMERA

8.00" NFPA MIN.

8.00" NFPA MIN.

401.75 (33'-5.75") APPROX OAL

CUSTOMER APPROVAL				Pierce MANUFACTURING INC.		JOB NO.	38150 01-02
APPROVED BY: _____						SCALE	1:24
DATE: _____						DATE	DATE
				TITLE	Pierce Pumper Approval Drawing	DRAWN BY	MMF
				FOR	Ohio Township Fire Department	CHECKED BY	COL
				DWG NO.	38150AD	SHEET SIZE	D
						SHEET NO.	1 OF 1

View File Created 24-AUG-2022 13:16:06