



- HOSEBED CAPACITIES**
- ① 200' OF 3.00" HOSE
 - ② 200' OF 3.00" HOSE
 - ③ 1000' OF 7.25" HOSE

ALUMINUM BODY

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 2. AIR INLET/OUTLET WITH DISCONNECT FITTING LOCATED ON THE DRIVER'S SIDE PUMP PANEL
- 3. ONE FULL WIDTH/DEPTH PAINTED ADJUSTABLE SHELF IN COMPARTMENTS LS1, LS2, LS3, RS1, RS2, & RS3
- 4. HUSKY 450 SINGLE AGENT INDUSTRIAL FOAM SYSTEM
- 5. BATTERY CHARGER INDICATOR ON DRIVER'S SEAT WITH BRACKET

		JOB NO.	39135
		SCALE	DATE
Pierce MANUFACTURING INC.		TITLE	5500 GPM, 1300 G TANK, 300 G WATER, 1000 G FOAM
		FOR	PIERCE STOCK APPLETON, WI
		DWG NO.	39135AD
		CHECKED BY	KLH
		SHEET SIZE	SHEET NO.
		DATE	1 OF 1

REV	DATE	BY	CH	VELOCITY
22SEP25	LST	AST		CHASSIS DATA
11JUN25	LST	AST		MAKE
05MAR25	LST	AST		MODEL