



- HOSEBED CAPACITIES**
- ① - 200' OF 1.75" DJP HOSE (TOP)
200' OF 2.50" DJP HOSE (BOTTOM)
 - ② - 200' OF 1.75" DJP HOSE (TOP)
400' OF 2.50" DJP HOSE (BOTTOM)
 - ③ - 500' OF 2.50" DJP HOSE
 - ④ - 700' OF 2.50" DJP HOSE
 - ⑤ - 700' OF 4.00" LDH HOSE

ALUMINUM BODY

SIDE ROLL PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- 2. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 3. BATTERY CHARGE INDICATOR LOCATED NEAR DRIVER'S SEAT RISER
- 4. INLET/OUTLET W/DISCONNECT COUPLING LOCATED PER SHOP ORDER

		JOB NO.	39827
		SCALE	1:24
MANUFACTURING INC.		DATE	
		DRAWN BY	BTH
PIERCE		CHECKED BY	JJR
		TITLE	2000GPM, 600G WATER TANK 161" 2G PUMPER, VELOCITY ESP
VELOCITY FR		FOR	WICHITA FIRE DEPARTMENT WICHITA, KANSAS
		DWG NO.	39827AD-SH1
REV	DATE	BY	CH
160CT25	03SEP25	MPM	JJR
06JUN25		JAM	JJR
		BTH	JJR