



ALUMINUM BODY MAXIMUM O.A.H. 120.00" SIDE ROLL & FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. S/STL SCUFFPLATE ON EACH CAB DOOR JAMB
2. S/STL SCUFFPLATE ON REAR OUTER CORNERS OF CAB
3. MOUNTING BASE FOR ANTENNA LOCATED PER SHOP ORDER
4. BATTERY CHARGER LOCATED IN CAB ON THE LEFT SIDE EMS COMPARTMENT WALL
5. PIERCE L.E.D. DUAL COMPARTMENT LIGHT STRIPS LOCATED PER SHOP ORDER
6. TWO 1-ZONE BRACKETS LOCATED AT REAR PER THE SHOP ORDER
7. STORAGE TUBE FOR HYDRANT WRENCH AND RUBBER MALLET LOCATED ON THE FRONT BUMPER PER SHOP ORDER

REV	DATE	BY	CH	VELOCITY
130CT25	LST	SGH		MAKE
10SEP25	LST	SGH		PIERCE
12AUG25	LST	BSE		MODEL

		JOB NO.	39997
		SCALE	1:24
MANUFACTURING INC.		TITLE	1500 GPM, 530 G TANK, 500 G WATER, 30 G FOAM TANK 177" PUC BODY, VELOCITY ESP ELECTRICAL SYSTEM
		FOR	ANAHEIM FIRE DEPARTMENT ANAHEIM, CALIFORNIA
DWG NO. 39997AD-SH1		DRAWN BY	LST
		CHECKED BY	SGH
SHEET NO. 1 OF 2		SHEET SIZE	D
		DATE	03JUN25