



- HOSEBED CAPACITIES**
- ① 200' OF 2.00" D.J. POLY HOSE WITH NOZZLE AND 6' OF 3.00" LEADER HOSE
  - ② 1000' OF 5.00" D.J. POLY HOSE
  - ③ 400' OF 3.00" D.J. POLY HOSE
  - ④ 250' OF 2.50" D.J. POLY HOSE
  - ⑤ 250' OF 1.75" D.J. POLY HOSE

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- 2. KUSSMAUL BATTERY CHARGER MOUNTED BEHIND DRIVER'S SEAT
- 3. BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER

CUSTOMER APPROVAL			
APPROVED BY: _____			
DATE: _____			
15OCT25	MPM	CHR	CHASSIS DATA
19SEP25	JER	CHR	MAKE
18JUL25	CDU	CDU	MODEL
REV	DATE	BY	CH

		JOB NO.	40082-01-02
		SCALE	1:24
TITLE 1500 GPM, 750G WATER TANK ENFORCER, HARD WIRED FOR GEORGETOWN FIRE DEPARTMENT GEORGETOWN, KENTUCKY		DRAWN BY	JER
		CHECKED BY	CDU
DWG NO. 40082AD		SHEET SIZE	D
		SHEET NO.	1 OF 1