(2) TRIPLE AIR BOTTLE COMPARTMENTS WITH POLISHED DOORS

(2) CROSSLAY HOSE BEDS FOR 250' OF 2.00" D.J. HOSE WITH 2.00" PIPING AND SIDE OUTLETS

(2) FIRE RESEARCH SPA850 L.E.D. SCENE LIGHTS EACH SIDE

WHELEN PSTANK2 L.E.D. WATER LEVEL GAUGE EACH SIDE

114.00 (9'-6.00") APPROX O.A.H.

30.75

S/S LIGHT SHIELD

FREE FLOATING RUNNING BOARD HOSE TRAY

(1) WELDON 9186-8580-29 L.E.D. DIRECTIONAL/MARKER LIGHT EACH SIDE

EXHAUST MODIFIED FOR 5" X 7" DIFFUSER

(3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE

RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION

(2) WHELEN 6R8 L.E.D. WARNING LIGHTS IN A COMMON BEZEL EACH SIDE

(2) WHELEN 600 SERIES L.E.D. DIRECTIONAL/MARKER LIGHTS

(1) 6.00" INLET WITH 5.00" PIPING AND SWIVEL WITH 6" FNST X 5" STORZ ADAPTER

(1) 2.50" OUTLET WITH 2.50" PIPING

(1) FEDERAL Q2B SIREN

19.00" PAINTED CHICAGO STYLE BUMPER EXTENSION

(2) HADLEY AIR HORNS

RIGHT SIDE TRAY FOR 20' OF 5" HOSE

CENTER TRAY FOR 150' OF 1.75" HOSE

(2) WHELEN SA315P SPEAKERS WITH STAINLESS STEEL GRILLES

COMMAND ZONE ANTENNA

(1) HANNAY BOOSTER REEL WITH CAPACITY FOR 150' OF 1.75" BOOSTER HOSE AND 1.50" PIPING

46.00 | 63.50 | 66.50 | 34.75 | 25.50 | 17.50 SIDE SHEET POSTS

(1) HIVIZ FT-B-72-x-x L.E.D. VISOR LIGHT

WHELEN FREEDOM IV-Q 81" L.E.D. LIGHTBAR

70.00

136.00

72.00

SURFACE DESIGNATION AND PATHWAY MARKINGS

(1) FRP L.E.D. FLOODLIGHT FOR DESIGNATED WALKWAY

27.50 CLEAR | 30.50 | 32.44 | 17.50

3.00" DELUGE OUTLET WITH XG12 EXTEND-A-GUN WITH 4-BOLT FLANG

ELKHART VULCAN 8500 MONITOR WITH ST-194 STACKED TIPS AND 282 A SHAPER

(3) ANTENNA MOUNTS

(1) WHELEN FREEDOM IV 21.50" L.E.D. LIGHTBAR EACH SIDE

(1) AIR PACK COMPARTMENT WITH POLISHED DOOR

FUEL FILL ACCESS

BATTERY CHARGER INDICATOR

AIR INLET WITH DISCONNECT COUPLING

20A 120V NEMA SHORELINE RECEPTACLE

8.25 | 9.25 | 17.00 | 9.00 | 79.25 | 20.00

61.00 | 30.00 | 64.75 | 47.50 | 31.50 | 27.13 R | 60.00 | 21.50 | 2.25 | 3.00 | 3.25

4.00

13.25 LADDER OVERHANG

67.50 (5'-7.50") APPROX O.A.H.

8.00" NFPA MIN. | 8.00" NFPA MIN.

1.50 | 31.50 | 35.50 | 2.00 | 48.00 | 66.00 | 41.50 FC | 16.00 | 42.00 | 28.00 | 97.00 | 70.00 | 187.50 WB | 117.50 CA | 86.00 | 8.00 | 383.75 (31'-11.75") APPROX OAL

(2) ZIAMATIC SAC-44-E FOLDING WHEEL CHOCKS

HITCH RECEIVER WITH POWER EACH SIDE

(1) 0.25" PERMANENT HOSE BED DIVIDER

(2) WHELEN L31 L.E.D. BEACON LIGHTS

(2) WHELEN TLI L.E.D. WARNING LIGHTS

(2) TROUGHS FOR (2) 6"X10' HARD SUCTION HOSES (CTF)

(2) WHELEN M9 L.E.D. SCENE LIGHTS

PIERCE CAMERA SYSTEM WITH REAR AND SIDE VIEW CAMERAS

CUP SWITCH FOR HOSE BED LIGHTS

(2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS

REAR HITCH RECEIVER WITH POWER

HOSEBED CAPACITIES

1. 250' OF 2.50" D.J. POLY HOSE
2. 1000' OF 5.00" D.J. POLY HOSE
3. 500' OF 2.50" D.J. POLY HOSE
4. 300' OF 3.00" D.J. POLY HOSE

33.63 | 9.25 | 13.88 | 11.25 | 17.00 | 14.00 | 43.50 | 39.00 | 51.00 | 89.00 | 72.00 | 38.00 | 36.00 | 25.75 | 4.00 | 1.75

(2) HOSEBED DIVIDERS

(1) 10' FOLDING 585A IN TROUGH

ALCO-LITE LADDERS: (1) 24' 2 SECTION PEL (1) 14' ROOF PRL

(2) 2.50" OUTLETS

14.00 | 68.00 | 14.00 | 28.00 | 40.00 | 28.00 | 96.00

5'-7"

WITH 6.00" FNST X 5.00" STORZ ELBOW

ALUMINUM BODY | MAXIMUM O.A.L. 384" | MAXIMUM O.A.H. 114.00" | SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. DEF TANK MOUNTED UNDER CAB ON THE DRIVER'S SIDE
2. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
3. TWO 15/20A 120V RECEPTACLE LOCATED PER ORDER

REV	DATE	BY	CH
B	21JAN26	BTH	ARG
A	05NOV25	BTH	SIZE

CHASSIS DATA
MAKE: PIERCE
MODEL: VELOCITY

Pierce MANUFACTURING INC.

TITLE: 1500GPM, 750G WATER TANK 152" 2G PUMPER, VELOCITY ESP
FOR: BERLIN TOWN OF BERLIN, CONNECTICUT
DWG NO.: 40325AD

JOB NO.: 40325
SCALE: 1:24
DATE: 300CT25
DRAWN BY: BTH
CHECKED BY: SZE
SHEET SIZE: D
SHEET NO.: 1 OF 1

View File Created 23-JAN-2026 08:01:21