

PUMPER, PUC

BODY

Pumper, PUC, Aluminum

CHASSIS

Enforcer Chassis, PUC

ELECTRICAL SYSTEM

Hard Wired

CHASSIS

AXLE, FRONT, CUSTOM

23,000 Lb Dana Axle

AXLE, REAR

31,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 6th Gen, 3000 EVS P

BUMPER

19" Extended Pointed Steel

CAB

7010 Enforcer Cab, PUC

BODY

TOTAL TANK CAPACITY

750 Gallon Poly Tank

WATER CAPACITY

750 Gallons of Water

FOAM CELL CAPACITY

Foam Cell Not Required

COMPT, PUMPER, REAR

29.50" FF Rollup Rear Compt w/Tailboard, PUC

COMPT, PUMPER, LEFT SIDE

214" Rollup Full Height & Depth Front & Rear, PUC

COMPT, PUMPER, RIGHT SIDE

214" Rollup Full Height & Depth Front & Rear, PUC

FIRE SUPPRESSION

PUMPHOUSE

Control Zone, PUC

PUMP

1500 GPM Pierce PUC

CROSSLAYS, 1.50"

(2) 1.50", Poly Trays, 200'

CROSSLAYS, 2.50"

(1) 2.50", Poly Tray, 200'

SPEEDLAYS

GENERATOR

HARRISON 3.6 kW MSV 120V

FOAM SYSTEM

Foam System Not Required

SAFETY

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. SHORELINE RECEPTACLE WITH KUSSMAUL AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB

2. AIR INLET WITH DISCONNECT COUPLING RECESSED IN THE DRIVER SIDE STEPPWELL

3. BATTERY CHARGER LOCATED PER ORDER

4. BATTERY CHARGE INDICATOR LOCATED ON DRIVER SEAT RISER

5. SIX ADJUSTABLE SHELVES LOCATED PER ORDER

6. ONE FLOOR MOUNTED SLIDE-OUT TRAY LOCATED PER ORDER

7. ONE SWING-OUT TOOLBOARD LOCATED PER ORDER

8. CIRCUIT BREAKER PANEL LOCATED PER ORDER

9. COMPRESSOR LOCATED PER ORDER

10. ON-SPOT AUTOMATIC TIRE CHAINS

Side View Labels:

- (1) WHELEN M6 L.E.D. WARNING LIGHT EACH SIDE
- (2) HANNAY CABLE REELS WITH 250' OF 10/3 CABLE (MODEL: E1620-17-18)
- OIL DRY HOPPER
- (1) STOKES BASKET 9 X 25 X 48
- (4) WHELEN M4 WATER LEVEL GAUGE LIGHTS EACH SIDE
- (3) HIVIZ GESM L.E.D. SCENE LIGHTS
- 120.50 (10'-1") APPROX O.A.H.
- 42.00
- 42.00
- RS2
- RS3
- RS4
- RS1

Top View Labels:

- 96.00
- 75.00
- 15.00
- 20.00
- 155.50
- 175.50
- 96.00
- 15.00
- 84.00 TRAY
- 14.12
- 4.00
- 5.50
- 31.00
- 50.50
- 60.00
- 30.00
- 32.00
- 37.75
- 61.75
- 20.00
- 27.13
- 22.25
- 33.00
- 33.00
- 61.63
- 4.25
- 8.00" NFPA MIN.
- 2.00
- 24.50
- 123.50
- 150.00 CA
- 90.50
- 12.00
- 220.00 WB
- 410.50 (34'-2.50") APPROX OAL

Rear View Labels:

- WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
- HIVIZ FT-B-72 L.E.D. VISOR LIGHT
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN M6 L.E.D. WARNING LIGHT AND (1) WHELEN 604T L.E.D. WARNING LIGHT IN A COMMON BEZEL EACH SIDE
- (1) 2.50" OUTLET WITH 2.50" PIPING AND SWIVEL
- (1) FEDERAL Q2B SIREN
- (2) AIR HORNS
- (1) WHELEN SA315P SPEAKER WITH 5/STL GRILLE
- CENTER HOSE TRAY FOR 150' OF 1.50" HOSE
- RIGHT HOSE TRAY FOR 100' OF 1.75" HOSE
- (2) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE

HOSEBED CAPACITIES

- ① 1000' OF 5.00" D.J. POLY HOSE
- ② 1000' OF 3.00" D.J. POLY HOSE

Rear View Labels (Continued):

- (1) 2.50" OUTLET
- (1) HOSE BED DIVIDER
- COMPARTMENT FOR (1) FOLDING LADDER DS (1) 6" DUO-SAFETY PIKE POLE (CTF) (1) 10' DUO-SAFETY PIKE POLE (CTF) (2) NY NOTCH PIKE POLE TUBES
- (2) WHELEN M6 L.E.D. WARNING LIGHTS
- (2) HIVIZ GESM L.E.D. SCENE LIGHTS 15" OPTICS
- LADDER STORAGE FOR (1) 24" DUO-SAFETY 2-SEC 900-A (1) 14" DUO-SAFETY ROOF 775-A FEET REARWARD
- CUP SWITCH FOR REAR SCENE LIGHTS
- STOP TAIL-BACK-UP & DIRECTIONAL L.E.D. LIGHTS IN A COMMON BEZEL
- (2) WHELEN M6 L.E.D. WARNING LIGHTS
- (1) WHELEN TAL65 L.E.D. TRAFFIC DIRECTING LIGHT
- (1) PIERCE BACKUP CAMERA (RECESSED)
- (1) CUP SWITCH FOR HOSE BED LIGHTS
- 21.00
- 33.00
- 23.00
- 21.00
- 30.25
- 1.75
- 17.75
- 36.63
- 29.50
- 28.00
- 42.00
- 28.00
- 98.00
- 92.00
- 70.00
- 5'-7"

TITLE	Pierce Pumper Approval Drawing	JOB NO.	40841
FOR	White Haven Fire Company #1	SCALE	1:24
DWG NO.	40841 AD	DRAWN BY	JAM
REV	DATE	CHECKED BY	MMF
BY	CH	SHEET SIZE	D
ENFORCER		SHEET NO.	1 OF 1

14APR25

JAM

GKH

PIERCE

11MAR25

JAM

GKH

PIERCE

14APR25

JAM

GKH

PIERCE

11MAR25

JAM

GKH

PIERCE