

PUMPER, PUC

BODY

Pumper, PUC, Aluminum

CHASSIS

Velocity Chassis, PUC (Big Block)

ELECTRICAL SYSTEM

MUX

CHASSIS

AXLE, FRONT, CUSTOM

22,800 Lb TAK-4 Axle

AXLE, REAR

27,000 Lb Meritor Axle

ENGINE

500 HP Cummins X12 Engine

TRANSMISSION

Allison 6th Gen, 4500 EVS P

BUMPER

22" Extended Pointed Steel

CAB

7010 Velocity FR Cab, PUC

BODY

TOTAL TANK CAPACITY

780 Gallon Poly Tank

WATER CAPACITY

750 Gallons of Water

FOAM CELL CAPACITY

30 Gallon Foam Cell

COMPT, PUMPER, REAR

33.50" FF Rollup Rear Compt w/Tailboard, PUC

COMPT, PUMPER, LEFT SIDE

189" Rollup Full Height & Depth Front & Rear, PUC

COMPT, PUMPER, RIGHT SIDE

189" Rollup Full Height & Depth Front & Rear, PUC

FIRE SUPPRESSION

PUMPHOUSE

Control Zone, PUC

PUMP

1500 GPM Pierce PUC

CROSSLAYS, 1.50"

(2) 1.50", Poly Trays, 200'

DEADLAYS, 2.50"

(1) 2.50", Poly Tray, 150'

SPEEDLAYS

GENERATOR

Generator Not Required

FOAM SYSTEM

Husky 3 Single Agent Foam System

SAFETY

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONE 2.50 OUTLET WITH 3.00 PIPING AND SWIVEL LOCATED ON TOP OF THE LEFT SIDE OF THE BUMPER

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE FRONT CAB CORNER

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED PER ORDER

5. BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SIDE FRONT CAB CORNER

6. SIX ADJUSTABLE SHELVES LOCATED PER ORDER

7. THREE ADJUSTABLE TILT/SLIDE-OUT TRAYS LOCATED PER ORDER

8. FOUR FLOOR MOUNTED SLIDE-OUT TRAYS LOCATED PER ORDER

9. ONE ALUMINUM TOOLBOARD ADDED TO SLIDE-OUT TRAY LOCATED PER ORDER

10. ONE VERTICAL PARTITION LOCATED PER ORDER

11. HANNAY MODEL SBEF4124-17-18 BOOSTER REEL FOR 100' OF 1.00" HOSE IN B1

