

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb Oshkosh Tak-4 Axle

AXLE, REAR

24,000 Lb Meritor Axle

ENGINE

450 HP Cummins L9

TRANSMISSION

Allison 6th Gen, 3000 EVS P

BUMPER

19" Extended Painted Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

750 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

152" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER PASS. SIDE

152" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

48" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

SpeedLays Not Required

GENERATOR

Generator Not Required

Foam System

Piping For Future Husky 3/12 Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water

Side Roll and Frontal Impact Protection

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONE 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF CAB

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT

5. FIVE ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER

6. TWO 120V RECEPTACLES LOCATED PER SHOP ORDER

7. FOUR FLOOR MOUNTED TRAYS LOCATED IN COMPARTMENT PER SHOP ORDER

Technical drawing of a fire truck showing side, top, and rear views with dimensions and callouts.

Side View Dimensions:

- Overall Length: 119.00 (9'-11") APPROX O.A.H.
- Overall Width: 88.00
- Wheelbase: 187.50 WB
- Overall Height: 70.00
- Running Board Hose Tray for 30" of 5.00" Hose
- 19.75 CLEAR, 22.25
- 8.00" NFPA MIN.
- 369.50 (30'-9.50") APPROX OAL

Top View Dimensions:

- Overall Length: 72.00
- Overall Width: 78.00
- Overall Height: 70.00
- Running Board Hose Tray for 30" of 5.00" Hose
- 10.50
- 136.00
- 10.50
- 72.00

Rear View Dimensions:

- Overall Length: 86.00
- Overall Width: 88.00
- Overall Height: 72.00
- Running Board Hose Tray for 30" of 5.00" Hose
- 8.00" NFPA MIN.
- 3.25
- 27.13
- 31.50
- 35.50
- 41.50 FC
- 42.00
- 28.00
- 16.00
- 8.00

Callouts:

- (1) HIWIZ FT-B-46 L.E.D. VISOR LIGHT
- MOUNTING PROVISIONS FOR WILL-BURT NIGHT SCAN POWERLITE
- WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN M6 L.E.D. WARNING LIGHT
- (1) WHELEN M62T L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE
- (1) FEDERAL Q28 STERN
- (2) HADLEY AIR HORNS
- (1) WHELEN SA31SP SPEAKER WITH S/STL GRILLE
- CENTER HOSE TRAY FOR 125" OF 1.75" HOSE
- HOSEBED CAPACITY
- BED 1: 750' OF 3.00" D.J. POLY HOSE
- BED 2: 1000' OF 5.00" D.J. POLY HOSE
- BED 3: 250' OF 3.00" D.J. POLY HOSE
- (2) HOSE BED DIVIDERS
- (2) WHELEN M9 L.E.D. WARNING LIGHTS EACH SIDE
- (2) HIWIZ FT-GESM L.E.D. SCENE LIGHTS
- (1) 2.50" OUTLET
- PIERCE REAR VIEW CAMERA RECESSED
- (1) CUP SWITCH FOR REAR SCENE LIGHTING
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS
- DUO- SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING S85A
- (2) ALUMINUM PIKE POLE TUBES
- (1) BACKBOARD (2" X 18" X 72")
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- 5'-7"
- (1) WHELEN TAL65 L.E.D. TRAFFIC DIRECTING LIGHT RECESSED

CUSTOMER APPROVAL					Pierce MANUFACTURING INC.		JOB NO.	41336
APPROVED BY: _____						TITLE	SCALE	DATE
DATE: _____							1:24	
				CHASSIS DATA	FOR	Pierce Pumper Approval Drawing	DRAWN BY	27SEP23
				MAKE		Pierce Stock Field Unit	AMI	
				PIERCE	DWG NO.		CHECKED BY	27SEP23
				MODEL			THS	
28NOV23	DATE	AMI	THS	ENFORCER		41336AD	SHEET SIZE	SHEET NO.
REV		BY	CH				D	1 OF 1

View File Created 28-NOV-2023 12:15:57