

TANKER BODY Tanker, Aluminum, Single Axle, Wet Side	
CHASSIS International HV607 Single Axle	
CHASSIS AXLE, FRONT, COMMERCIAL 16,000 Lb Front Axle	
AXLE, REAR, COMMERCIAL 31,000 Lb Rear Axle	
ENGINE 450 HP Cummins L9 Engine	
TRANSMISSION Allison 3000 EVS	
BUMPER 19" Extended, Steel PAINTED CHICAGO STYLE	
CAB International HV607 2-Door	
FUEL TANK 50 Gallon, Left Side, Aluminum	
CAB STEPS Steps as Provided by MFG	
BODY TOTAL TANK CAPACITY 2100 Gallon Poly Tank	
WATER CAPACITY 2100 Gallons of Water	
FOAM CELL CAPACITY Provisions for 25 Gallon Foam Cell	
COMPT, PUMPER, REAR Not Applicable	
COMPT, LEFT SIDE Single Axle, Low Side, LAP Doors	
COMPT, RIGHT SIDE Single Axle, Low Side, LAP Doors	
FIRE SUPPRESSION PUMPHOUSE 34" Control Zone Side Mount	
PUMP 1250 GPM Waterous CXPA	
CROSSLAYS, 1.50" (2) 1.50" Standard Capacity	
CROSSLAYS, 2.50" 2.50" Crosslay Not Required	
SPEEDLAYS Speedlays Not Required	
GENERATOR Generator Not Required	
FOAM SYSTEM PLUMBING FOR FUTURE FOAM SYSTEM	
NOTE DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.	

