



- HOSEBED CAPACITIES
- ① 300' OF 3.00" D.J. POLY HOSE
 - ② 1000' OF 5.00" D.J. POLY HOSE
 - ③ 500' OF 3.00" D.J. POLY HOSE
 - ④ OPEN BED

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 2. BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SIDE THROUGH
- 3. ONE 2.50" INLET WITH 2.50" PIPING LOCATED IN THE CENTER HOSE TRAY
- 4. ONE 120V RECEPTACLE LOCATED PER SHOP ORDER
- 5. PROVISIONS FOR FRONT INLET

CUSTOMER APPROVAL

| | |
|--------------------|---------|
| APPROVED BY: _____ | |
| DATE: _____ | |
| CHASSIS DATA | TITLE |
| MAKE | FOR |
| MODEL | DWG NO. |
| ENFORCER | |



1500GPM, 750G TANK, 725G WATER, 25G FOAM
152" PUMPER, HARD WIRED
PIERCE FIELD UNIT
APPLETON, WISCONSIN

43858AD

NFPA 1900
(2024)
COMPLIANT

| | |
|------------|-----------|
| JOB NO. | 43858 |
| SCALE | DATE |
| DRAWN BY | 16JUL25 |
| CHECKED BY | 18JUL25 |
| SHEET SIZE | SHEET NO. |
| D | 1 OF 1 |